

Date:	
Type:	
Firm Name:	
Project:	



Double Sided

EZBeam Energy Series

Everylite Datasheet Ver 2.1
Revision Date 08/2019



Features

- EZBeam Double Sided version for double-sided cabinets, signage and monuments
- Incredible 175° beam angle means better coverage and no hot spots allowing the product to be placed up to 24" between runs with a minimum 6" distance between sign face and module.
- Innovative optical lens technology allows to use fewer product per application saving both time and labor
- Available premounted on a bar or without the bar
- Available in 2, 3, 4, 5 ft. aluminum mounting bar with EZ middle connector which allows you to create virtually any desired length
- Aluminum mounting bar uses an end connector allowing EZBeam to be quickly and easily installed into signage applications
- Designed for new construction and direct retrofit
- 50,000 hours rated lifetime
- UL, CE and RoHS



EZBeam Energy Double Sided Parameters (6 watt version)

Item#	Color	Peak Wave Length	#module(s)	Lm/unit	Lm/ft	Lm/W	W/unit	W/ft	Input Voltage	Viewing Angle	Waterproof
EZ-3D-W6CL-DS	Pure White	6500K	1	550	550	92	6	6	12	175°	IP65
EZ-2F-W6CL-EG	Pure White	6500K	2	1100	550	92	12	6	12	175°	IP65
EZ-3F-W6CL-EG	Pure White	6500K	3	1650	550	92	18	6	12	175°	IP65
EZ-4F-W6CL-EG	Pure White	6500K	4	2200	550	92	24	6	12	175°	IP65
EZ-5F-W6CL-EG	Pure White	6500K	5	2750	550	92	30	6	12	175°	IP65

Power Supply Maximum Loading Capacity*

Power Supply	20W	30W	60W	100W	150W	240W
By Module	3 mods	4 mods	9 mods	15 mods	22 mods	36 mods
By Footage	3 ft	4 ft	9 ft	15 ft	22 ft	36 ft

*Due to voltage drop, a maximum of 7 modules can be run before power needs to be reintroduced into the line of modules.

Drawing

Unit: inches

